RNAV (GPS) RWY 28R

MONTGOMERY-GIBBS EXEC (MYF)

WAAS CH 45710 W28A	APP CRS 281°	Rwy Idg 3399 / TDZE 423 / Apt Elev 427

RNP APCH.

Rwy 28R helicopter visibility reduction below ¾ SM NA.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.

MALSR

MISSED APPROACH: Climb to 3000 direct JOPDO and on track 327° to CARIF and hold.

ATIS	SOCAL APP CON	MONTGOMERY TOWER ★	GND CON	CLNC DEL	UNICOM
126.9	124.35 279.625	119.2 (CTAF) L 269.4 (Rwys 5, 10L/R, 23, 28L) 125.7 269.4 (Rwy 28R)	118.225	123.725	123.075



ELEV 427 TDZE 423



REIL Rwy 28L
MIRL Rwy 10L-28R



CATEGORY	A	B	C	D
LPV DA	673-¾	250 (300-¾)	NA	
LNAV/VNAV DA	750-¾	327 (400-¾)	NA	
LNAV MDA	840-¾	417 (500-¾)	NA	
CIRCLING	920-1	493 (500-1)	NA	

SW-3, 20 MAR 2025 to 17 APR 2025