

LOC I-MJX 109.9	APP CRS 063°	Rwy Idg 5835 TDZE 81 Apt Elev 86
---------------------------	------------------------	---

ILS or LOC RWY 6
OCEAN COUNTY (MJX)


▼ Circling Rwy 14, 32 NA at night. Inop table does not apply to S-ILS 6. For inop ALS, increase S-LOC 6 Cats A/B and S-LOC 6 XOQUR Fix minimums Cats A/B visibility to 1/2 mile. When local altimeter setting not received, use Mc Guire Fld Joint Base Mc Guire Dix (Lakehurst) altimeter setting and increase all DA 41 feet and all MDA 60 feet; increase S-LOC 6 Cats C/D and Circling Cat C visibility 1/8 mile, Cat D 1/4 mile; increase XOQUR Fix minimums S-LOC 6 Cat C/D visibility 1/8 mile and Circling Cat D 1/4 mile. For inop ALS when using Mc Guire Fld (Joint Base Mc Guire Dix Lakehurst) altimeter setting, increase S-ILS 6 all Cats visibility to 3/8 and S-LOC 6 Cats A/B and S-LOC 6 XOQUR Fix minimums Cats A/B visibility to 1, Cats C/D visibility to 1/8. Rwy 6 helicopter visibility reduction below 3/4 SM NA.

MALSR

MISSED APPROACH:
Climb to 600 then
climbing right turn to
1900 direct CYN
VORTAC then on
CYN R-260 to SOITE
INT/CYN 2.6 DME
and hold.

AWOS-3PT
119.875


MC GUIRE APP CON
126.475 363.8

UNICOM
122.7 (CTAF) 

*720 when using Joint Base Mc Guire
Dix Lakehurst altimeter setting.

One Minute Holding Pattern

CATEGORY	A	B	C	D
S-ILS 6	331- ³ / ₄ 250 (300- ³ / ₄)			
S-LOC 6	660- ³ / ₄	579 (600- ³ / ₄)	660-1 ¹ / ₄	579 (600-1 ¹ / ₄)
 CIRCLING	660-1	574 (600-1)	660-1 ³ / ₄ 574 (600-1 ³ / ₄)	700-2 614 (700-2)
XOQUR FIX MINIMUMS (DUAL VOR RECEIVERS or DME REQUIRED)				
S-LOC 6	520- ³ / ₄	439 (500- ³ / ₄)	520- ⁷ / ₈	439 (500- ⁷ / ₈)
 CIRCLING	540-1 454 (500-1)	560-1 474 (500-1)	580-1 ¹ / ₂ 494 (500-1 ¹ / ₂)	700-2 614 (700-2)



MIRL Rwy 14-32 **L**
HIRL Rwy 6-24 **L**
REIL Rwy 14, 24 and 32 **L**

FAF to MAP 4.6 NM					
Knots	60	90	120	150	180
Min:Sec	4:36	3:04	2:18	1:50	1:32