


WAAS CH 40499 W21A	APP CRS 211°	Rwy Idg TDZE Apt Elev 7000 43 46
--	------------------------	--

RNAV (GPS) Y RWY 21

CHARLESTON AFB/INTL (CHS)

RNP APCH.	MISSED APPROACH: Climb to 3000 direct HERTZ and hold, continue climb-in-hold to 3000.
▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C or above 54°C.	

D-ATIS 124.75	CHARLESTON APP CON 120.7 306.925	CHARLESTON TOWER 126.0 239.0	GND CON 121.9 348.6	CLNC DEL 127.325 291.65	CPDLC
-------------------------	--	--	-------------------------------	-----------------------------------	-------



3000

HERTZ

↑

✦

*LNAV only.

AKETE

1700

ALGOE

4 NM Holding Pattern

031°

6000

3000

211°

1700

GP 3.00°

TCH 50

RW21

1.3 NM

3.8 NM

6.8 NM

1.3 NM to RW21

CATEGORY	A	B	C	D
LPV DA		293-¾	250 (300-¾)	
LNAV/VNAV DA		382-1	339 (400-1)	
LNAV MDA	500-1	457 (500-1)	500-1⅓	457 (500-1⅓)
CIRCLING	540-1	494 (500-1)	540-1½ 494 (500-1½)	740-2¼ 694 (700-2¼)

