

DAYTON EIGHT DEPARTURE
(DAY8.DAT) 16MAY24

JAMES M COX DAYTON INTL (DAY)
DAYTON, OHIO

ATIS
125.8
CLNC DEL
121.75
GND CON
121.9
DAYTON TOWER
119.9 257.7
COLUMBUS DEP ON
118.85 305.2 (091°-180°)
134.45 323.15 (181°-090°)

TAKEOFF MINIMUMS:
Rwy 6L/R, 24L/R, 36: Standard.
Rwy 18: 300-1 or standard with a minimum
climb of 305' per NM to 1300.

RADAR required.

TOP ALTITUDE:
5000

PIONS

DRYER
113.6 DJB
Chan 83

N

KLOEE

REELS

FORT WAYNE
117.8 FWA
Chan 125

ROSEWOOD
117.5 ROD
Chan 122

MUNCIE
114.4 MIE
Chan 91


DAYTON
114.5 DQN
Chan 92

APPLETON
116.7 APE
Chan 114

BRICKYARD
116.3 VHP
Chan 110

YELLOW BUD
112.5 XUB

MSA DQN 25 NM
3100



(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

(DAY8.DAT) 24137
DAYTON EIGHT DEPARTURE

AL-107 (FAA)

JAMES M COX DAYTON INTL (DAY)
DAYTON, OHIO



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 6L/R: Climb on heading 061°, thence....

TAKEOFF RUNWAY 18: Climb on heading 185°, thence....

TAKEOFF RUNWAYS 24L/R: Climb on heading 241°, thence....

TAKEOFF RUNWAY 36: Climb on heading 005°, thence....

....or assigned RADAR vectors to join assigned route/fix. All aircraft maintain 5000 or filed altitude if lower. Expect clearance to requested altitude/flight level 10 minutes after departure. Appropriate departure control frequency will be assigned by ATC. Aircraft filed over APE VORTAC, expect vectors to intercept APE R-260.

EC-2, 17 APR 2025 to 15 MAY 2025

EC-2, 17 APR 2025 to 15 MAY 2025