

WAAS CH 50106 W36A	APP CRS 356°	Rwy Idg TDZE 899 Apt Elev 901
--	------------------------	---

RNAV (GPS) RWY 36

HECTOR INTL (FAR)


RNP APCH.

Baro-VNAV NA below -16°C (4°F). For inop MALSR, increase LPV Cat E visibility to RVR 4000, and increase LNAV/VNAV and LNAV Cat E visibility to 1¾ mile.

MALSR

MISSED APPROACH: Climb to 3500 direct MULEE and hold.

ATIS 124.5 379.2	FARGO APP CON 120.4 377.15	FARGO TOWER 133.8 290.4	GND CON 121.9 348.6	CLNC DEL 121.9 348.6
----------------------------	--------------------------------------	-----------------------------------	-------------------------------	--------------------------------



8 NM Holding Pattern

KOBME

HUBET

3500

GP 3.00° TCH 55

356°

356°

356°

2600

6.5 NM

3.7 NM

1.4 NM

RW36

*1.4 NM to RW36

*LNAV only.

MULEE

CATEGORY	A	B	C	D	E
LPV DA	1150/24 251 (300-½)				
LNAV/VNAV DA	1360/50 461 (500-1)		1360/60 461 (500-1¼)		
LNAV MDA	1420/24 521 (600-½)	1420/50 521 (600-1)	1420/60 521 (600-1¼)		
CIRCLING	1420-1 519 (600-1)	1520-1¾ 619 (700-1¾)	1620-2¼ 719 (800-2¼)	1620-2½ 719 (800-2½)	

ELEV 901

TDZE 899

HIRL Rwy 18-36

REIL Rwy 9 and 27

MIRL Rwy 9-27 and 13-31