


WAAS CH 90504 W22A	APP CRS 223°	Rwy Idg TDZE 652 Apt Elev 680
--	------------------------	---

RNAV (GPS) RWY 22R

CHICAGO O'HARE INTL (ORD)

▼ ▲ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C (-7°F) or above 39°C (102°F). Simultaneous approach authorized with Rwy 22L. DME/DME RNP-0.3 NA. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.	MALSR A5	MISSED APPROACH: Climb to 4000 direct EVRSN and on track 263° to DPA VOR/DME and hold.
--	--	---

D-ATIS 135.4 282.225	CHICAGO APP CON 119.0 292.125	O'HARE TOWER 126.9 348.0	GND CON 124.125 (TWR NORTH) 118.05 (TWR SOUTH) 226.675 (ALL TWRs)	(TWR CENTER) 121.75 (OBND) 121.9 (IBND)	CLNC DEL 121.6	CPDLC
--	--	------------------------------------	---	---	--------------------------	-------



4000 EVRSN	DPA	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 69).			
↑	tr 263°				
* LNAV only.					
	PALIE 1.7 NM to RW22R	RIDGE	NOLEN	FNUCH	
	*1 NM to RW22R				
	1200	2200	5000	7000	GP 3.00° TCH 49
	1 NM	0.7	3 NM	10.4 NM	6.9 NM
CATEGORY	A	B	C	D	
LPV DA		852/18	200 (200-½)		
LNAV/VNAV DA		972/32	320 (300-¾)		
LNAV MDA	1040/24	388 (400-½)	1040/35	388 (400-¾)	
CIRCLING	1220-1	540 (600-1)	1220-1½ 540 (600-1½)	1460-2½ 780 (800-2½)	

