

WAAS
CH **86509**
W36A

APP CRS
360°

Rwy Idg
TDZE **653**
Apt Elev **656**

RNAV (GPS) RWY 36

LA CROSSE RGNL (LSE')

RNP APCH.

▽


⚠

❄ -22°C

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -27° C or above 54° C. When local altimeter setting not received, use Winona altimeter setting: increase LPV DA to 1006 feet, LNAV/VNAV DA to 1256 feet and all MDA 60 feet. Increase LPV all Cats visibility ¼ SM, LNAV/VNAV all Cats visibility ¼ SM, LNAV Cats C/D visibility ¼ SM and Circling Cat C visibility ¼ SM. Circling to Rwy 22 NA at night. Baro-VNAV and VDP NA when using Winona altimeter setting.

MISSED APPROACH:
Climb to 3500 direct POGOC and hold.

ATIS 124.95	MINNEAPOLIS CENTER 128.6 363.0	LA CROSSE TOWER★ 118.45 (CTAF) 251.075	GND CON 121.8	UNICOM 122.95
-----------------------	--	--	-------------------------	-------------------------



4 NM Holding Pattern

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 28).

3500 POGOC

3000 ←180° 360°→

GP 3.00° TCH 50

PKRNA

CIVMI

2500

*LNAV only.

*1.5 NM to RW36

RW36

8 NM

4.1 NM

1.5 NM

CATEGORY	A	B	C	D
LPV DA	953-1 300 (300-1)			
LNAV/VNAV DA	1203-2 550 (600-2)			
LNAV MDA	1140-1 487 (500-1)	1140-1¼ 487 (500-1¼)	1140-1½ 487 (500-1½)	
CIRCLING	1140-1 484 (500-1)	1460-1 804 (900-1)	1760-3 1104 (1200-3)	1820-3 1164 (1200-3)

ELEV 656

D

TDZE 653

MIRL Rwy 13-31

HIRL Rwy 4-22 and 18-36

REIL Rwy 13, 31 and 36

Diagram of runway layout with distances (e.g., 87.42 x 150, 60.82 x 150, 51.95 x 150) and altitudes (e.g., 81, 712, 724). A 360° heading is indicated.