

ILS or LOC RWY 28L
CAPITAL REGION INTL (LAN)

MISSED APPROACH: Climb to 2500 then climbing left turn to 3000 on VIO VOR/DME R-100 to UNSUN/VIO 18.5 DME and hold.



ILS Plan View: The plan view shows the ILS alignment from 276° to 096°. Key features include:

- ILS 28L:** 10R, 10L, 10C, 10D, 10E, 10F, 10G, 10H, 10I, 10J, 10K, 10L, 10M, 10N, 10O, 10P, 10Q, 10R, 10S, 10T, 10U, 10V, 10W, 10X, 10Y, 10Z.
- Visual Aids:** 10R, 10L, 10C, 10D, 10E, 10F, 10G, 10H, 10I, 10J, 10K, 10L, 10M, 10N, 10O, 10P, 10Q, 10R, 10S, 10T, 10U, 10V, 10W, 10X, 10Y, 10Z.
- Distances:** 3601 X 75, 8506 X 150, 5003 X 120.
- Frequency:** 109.36 MHz.

Category	A	B	C	D
S-ILS 28L*	1052/24 200 (200-½)			
S-LOC 28L	1300/24 448 (500-½)		1300/45 448 (500-¾)	
Circling	1380-1 519 (600-1)		1600-2 739 (800-2)	1760-3 899 (900-3)

EC-1, 17 APR 2025 to 15 MAY 2025