

LOC Y RWY 21L

LOC I-DIQ

109.1

APCH CRS

209°

Rwy Idg 21L

10,051

TDZE

1865

Arpt Elev

1869

Rwy Idg 21R

10,120

TDZE

1869

AL-227 [USAF]

NELLIS AFB (KLSV)

RADAR or DME required.

ALSF-1

A1

MISSED APPROACH: Climb to 8000, intercept the LAS VORTAC R-018 to 10.3 DME (IREEN), then to LAS and hold, continue climb in hold to 8000.

ATIS

270.1

APP CON

124.95 273.55

TOWER

132.55 327.0

GND CON

121.8 275.8

CLNC DEL

120.9 289.4

FOR USE BY NELLIS AFB
ASSIGNED AIRCRAFT ONLY

9908

7000

(IAF) ZAPVO LAS 33.8

(IF) BALBE LAS 24.6

WOXEK LAS 19.6

JEGET LAS 17.9

FESDI LAS 16.6

RADAR 2214

LATPE LAS 14.6

IREEN LAS 10.3

LOCALIZER 109.1

I-DIQ

LAS VEGAS

116.9 LAS

Chan 116

EMERG SAFE ALT 100 NM 14,000

8000

LAS R-018

IREEN 10.3

LAS

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 54).

VORTAC

ENIYO 12.4

13.4

2760

3600

4000

4400

5700

3.41° TCH 54 (from FESDI)

10,120 x 200

10,051 x 150

31 3R

A1

P

P

P

P

P

H

H

TWR

21L/21R

209°

HIRL all rwys

F knots

60

90

120

150

180

F /min:sec

4:12

2:48

2:06

1:41

1:24

SW-4, 17 APR 2025 to 15 MAY 2025

SW-4, 17 APR 2025 to 15 MAY 2025