

OAKLAND CENTER
127.8 353.5
ATIS
124.05
CLNC DEL
127.85
GND CON
121.7
NAPA TOWER★
118.7 (CTAF) 257.8

TOP ALTITUDE:
ASSIGNED BY ATC

TAKEOFF MINIMUMS
Rwy 1L: Standard with minimum climb of 420' per NM to 2900.
Rwy 1R: Standard with minimum climb of 460' per NM to 3000.
Rwy 6: Standard with minimum climb of 430' per NM to 1600.
Rwy 19L: Standard with minimum climb of 320' per NM to 1500.
Rwy 19R: Standard with minimum climb of 330' per NM to 1600.
Rwy 24: Standard with minimum climb of 255' per NM to 1300.

RED BLUFF
115.7 RBL
Chan 104

WILLIAMS
114.4 ILA
Chan 91

MENDOCINO
112.3 ENI
Chan 70

SACRAMENTO
115.2 SAC
Chan 99

SCAGGS ISLAND
112.1 SGD
Chan 58

POINT REYES
113.7 PYE
Chan 84

LINDEN
114.8 LIN
Chan 95

SAUSALITO
116.2 SAU
Chan 109

CONCORD
117.0 CCR
Chan 117

OAKLAND
116.8 OAK
Chan 115

(CONTINUED ON FOLLOWING PAGE)

NOTE: RADAR required.
NOTE: Chart not to scale.

SW-2, 17 APR 2025 to 15 MAY 2025

SW-2, 17 APR 2025 to 15 MAY 2025



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 1L/R: Climb on heading 006° (or climbing left turn on ATC assigned heading 186° CW 006°); thence. . . .

TAKEOFF RUNWAY 6: Climbing right turn on assigned heading between 130° CW 242°; thence. . . .

TAKEOFF RUNWAYS 19L/R: Climb on heading 186° (or ATC assigned heading 130° CW 270°); thence. . . .

TAKEOFF RUNWAY 24: Climb on heading 242° (or ATC assigned heading 130° CW 270°); thence. . . .

. . . . expect vectors to join assigned route. Maintain ATC assigned altitude; expect filed altitude/flight level ten minutes after departure.

LOST COMMUNICATIONS

If not in contact with Oakland Center after reaching 4000, proceed to the SGD VORTAC and hold.

SW-2, 17 APR 2025 to 15 MAY 2025

SW-2, 17 APR 2025 to 15 MAY 2025