

WAAS CH 90299 W20A	APP CRS 202°	Rwy Idg TDZE 1194 Apt Elev 1194
--	------------------------	---

RNAV (GPS) RWY 20

WALLA WALLA RGNL (ALW)

RNP APCH - GPS.

▽


⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C or above 54°C. For inop ALS, increase LNAV/VNAV visibility to 1% SM.
*RVR 1800 authorized with use of FD or AP or HUD to DA.

MALS

MISSED APPROACH:
Climb to 4000 direct CILON and hold.

ASOS 135.875	SPOKANE APP CON★ 133.15 379.15	WALLA WALLA TOWER★ 118.5 (CTAF) 289.4	GND CON 121.6 289.4	UNICOM 122.95
------------------------	--	---	-------------------------------	-------------------------



4000	CILON	WACKE 3.7 NM to RW20	COSUV 3200	KIMI 5 NM Holding Pattern
2.9 NM to RW20	0.9 NM	2.4 NM	5.9 NM	
2420	3200	3200	10000 4600	GP 3.00° TCH 50
CATEGORY	A	B	C	D
LPV DA*	1394/24	200 (200-½)		
LNAV/VNAV DA	1773-1¼	579 (600-1¼)		
LNAV MDA	2160/40 966 (1000-¾)	2160/55 966 (1000-1)	2160-2½	966 (1000-2½)
CIRCLING	2160-1¼ 966 (1000-1¼)	2160-1½ 966 (1000-1½)	2160-3 966 (1000-3)	2300-3 1106 (1200-3)

