

TOP ALTITUDE:
10000

SPOKANE DEP CON★
123.8 263.15
ATIS
125.25
CLNC DEL
121.9
GND CON
121.9
YAKIMA TOWER★
133.25 257.8

SEATTLE
116.8 SEA :--:
Chan 115

WENATCHEE
114.35 EAT :--:
Chan 90(Y)

EPHRATA
112.6 EPH :--:
Chan 73

MOSES LAKE
115.0 MWH :--:
Chan 97

SPOKANE
115.5 GEG :--:
Chan 102

ELLENSBURG
117.9 ELN :--:
Chan 126

R-6714D

V448

R-6714A

R-6714B

R-6714C

R-108

4600

V4-298

108°

288°

094°

320°

BATTLE GROUND
116.6 BTG :--:
Chan 113

YAKIMA
116.0 YKM :--:
Chan 107

PASCO
113.75 PSC :--:
Chan 84(Y)

WALLA WALLA
116.4 ALW :--:
Chan 111

PENDLETON
114.7 PDT :--:
Chan 94

KUICKITAT
112.3 LTJ :--:
Chan 70



TAKEOFF MINIMUMS

- Rwy 4: NA-obstacles.
Rwy 9: Standard with minimum climb of 360' per NM to 4400.
Rwy 22: Standard with minimum climb of 495' per NM to 6000.
Rwy 27: Standard with minimum climb of 495' per NM to 6000.

NOTE: RADAR required.

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 9: Climb heading 094° for vector to assigned route/fix. Thence
TAKEOFF RUNWAYS 22, 27: Climbing right turn heading 320° for vector to assigned route/fix. Thence

. . . . maintain 10000 or assigned lower altitude. Expect clearance to filed altitude 5 minutes after departure.

LOST COMMUNICATIONS

If no transmissions are received for one minute after departure:

RUNWAY 9: Climb heading 094° and outbound YKM VORTAC R-108.

RUNWAYS 22, 27: Climbing right turn direct YKM VORTAC and outbound YKM R-108, eastbound aircraft V4-V298 continue on course, all other departures continue climb on YKM R-108, until 4600, then climbing right turn direct YKM VORTAC and hold to cross YKM VORTAC at or above MEA or MCA for route of flight.

NW-1, 17 APR 2025 to 15 MAY 2025

NW-1, 17 APR 2025 to 15 MAY 2025