


WAAS CH 45532 W24A	APP CRS 240°	Rwy ldg TDZE 592 Apt Elev 592
--	------------------------	---

RNAV (GPS) Z RWY 24
NIAGARA FALLS INTL (IAG)

▼ DME/DME RNP-0.3 NA. When local altimeter setting not received, use Buffalo Niagara Int'l altimeter setting and increase all MDA 60 feet; increase LP Cats C and D visibility ¼ SM, LNAV Cats C and D visibility ½ SM, and Circling Cat C and D visibility ¼ SM. Rwy 6, 10R, 24, 28L helicopter visibility reduction below 1 SM NA. Straight-in Rwy 24 NA at night, Circling Rwy 6, 10R, 24, 28L NA at night. *Missed approach requires a minimum climb of 265 feet per NM to 2120; if unable to meet climb gradient, see RNAV (GPS) Y RWY 24.					
ATIS 120.8 269.4	BUFFALO APP CON 126.5 317.6	NIAGARA TOWER★ 118.5 (CTAF) 0 349.0	GND CON 125.3 275.8	CLNC DEL 119.25 251.1	UNICOM 122.95



ELEV 592 D TDZE 592		1400 3600 ZUPUV		4 NM Holding Pattern	
240°		YEPNU 1.7 NM to RW24		WUVBI	
1180		2300		3600	
1.7 NM		3.5 NM		7.6 NM	
CATEGORY	A	B	C	D	
LP MDA*	1000-1	408 (500-1)	1000-1½	408 (500-1½)	
LNAV MDA*	1020-1	428 (500-1)	1020-1¼	428 (500-1¼)	
CIRCLING	1100-1	508 (600-1)	1280-2 688 (700-2)	1280-2½ 688 (700-2½)	