


WAAS CH 97505 W04A	APP CRS 041°	Rwy Idg 5750 TDZE 1496 Apt Elev 1500
--	------------------------	---

RNAV (GPS) RWY 4
JAMESTOWN RGNL (JMS)

T
A For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C (-5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA.

MISSED APPROACH: Climb to 3300 direct
CALOT and hold.

ASOS 118.425	MINNEAPOLIS CENTER 124.2 270.3	UNI/COM 123.0 (CTAF) 0
------------------------	--	----------------------------------



VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 22).

4 NM Holding Pattern

3700 ← 221°

041° →

GP 3.00° TCH 45

GANEY

FARSA

3300

DOCAN 2.5 NM to RW04

*1.5 NM to RW04

*2340

RW04

*LNAV only

CATEGORY	A	B	C	D
LPV DA	1746-1 250 (300-1)			
LNAV/VNAV DA	1930-1½ 434 (500-1½)			
LNAV MDA	2000-1 504 (500-1)		2000-1½ 504 (500-1½)	
C CIRCLING	2000-1 500 (500-1)		2000-1½ 500 (500-1½)	2300-2½ 800 (800-2½)

