

BOSTON DEP CON
124.1 343.6
ATIS 119.95
CLNC DEL
121.8
GND CON
121.8
NORWOOD TOWER ★
126.0 (CTAF)

KENNEBUNK
117.1 ENE ---
Chan 118



PEASE

MANCH △

CAMBRIDGE
115.0 CAM ---
Chan 97


RADAR required.
DME required: BLZZR, BRUWN, HYLND, PATSS, REVSS DEPARTURES

TOP ALTITUDE:
2000

SYRACUSE
117.0 SYR ---
Chan 117

CHESTER
115.1 CTR ---
Chan 98

BARNES
113.0 BAF ---
Chan 77



REVSS △ R-285

GLYDE △

BLZZR △

PATSS

PROVIDENCE
115.6 PVD ---
Chan 103

HYLND △

LBSTA △

BOSTON
112.7 BOS ---
Chan 74

CELTK △

FRILL △

DUNKK △

BURDY △

FREDO △

SSOXS △

BRUWN △

MARCONI
114.7 LFV ---
Chan 94

MARTHAS VINEYARD
114.5 MVY ---
Chan 92

NANTUCKET
116.2 ACK ---
Chan 109

BUZRD

SANDY POINT
117.8 SEY ---
Chan 125

TAKEOFF MINIMUMS:

- Rwy 10: 400-2½ or standard with minimum climb of 440'/NM to 300.
- Rwy 17: Standard.
- Rwy 28: Standard with minimum climb of 385'/NM to 400.
- Rwy 35: Standard with minimum climb of 260'/NM to 1800.

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 10: Climb on heading 104° to 1100, then as assigned by ATC, thence

TAKEOFF RUNWAY 17: Climb on assigned heading, thence...

TAKEOFF RUNWAY 28: Climb on heading 284° to 700, then as assigned by ATC, thence

TAKEOFF RUNWAY 35: Climb on heading 280° CW 330° as assigned by ATC, thence

. . . . for RADAR vectors to assigned route/NAVAID/fix. Maintain 2000. Expect clearance to filed altitude/flight level within ten (10) minutes after departure.

- NOTE: BLZZR DEPARTURES expect vectors on BOS R-273.
- NOTE: BRUWN DEPARTURES expect vectors on BOS R-159.
- NOTE: CELTK DEPARTURES expect vectors on BOS R-114.
- NOTE: HYLND DEPARTURES expect vectors on BOS R-350.
- NOTE: PATSS DEPARTURES expect vectors on BOS R-260.
- NOTE: REVSS DEPARTURES expect vectors on BOS R-285.
- NOTE: SSOXS DEPARTURES expect vectors on BOS R-177.

NE-1, 17 APR 2025 to 15 MAY 2025

NE-1, 17 APR 2025 to 15 MAY 2025