

RNP APCH-GPS.

▼


▲

Inop table does not apply to LPV. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 7°C or above 54°C. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations.

MALSF

MISSED APPROACH: Climb to 1000 then climbing left turn to 3000 direct GEGEY and hold.

D-ATIS 135.0	MIAMI APP CON 133.775 285.6	FORT LAUDERDALE TOWER 119.3 257.8	GND CON 121.4	CLNC DEL 128.4	CPDLC
------------------------	---------------------------------------	---	-------------------------	--------------------------	-------



ELEV 65

D

TDZE 65

1000

3000

GEGEY

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 69).

WIKIR

4 NM Holding Pattern

YOBUS

2000

1.2 NM to RW28L

276°

096°

6000

2500

GP 3.00° TCH 53

1.2 NM

4.7 NM

5 NM

10L

66

28R

9000 X 150

8000 X 150

TWR 194

UP

DOWN

0.4%

1.0%

276°

CATEGORY	A	B	C	D
LPV DA	265/40	200 (200-¾)		
LNAV/VNAV DA	459/45	394 (400-⅞)		
LNAV MDA	500/40	435 (500-¾)	500/50	435 (500-1)
CIRCLING	680-1	615 (700-1)	800-2 735 (800-2)	800-2¼ 735 (800-2¼)

HIRL Rwy 10L-28R and 10R-28L