

WAAS CH 93730 W19B	APP CRS 194°	Rwy Idg 5004 TDZE 787 Apt Elev 787
--	------------------------	---

RNAV (GPS) Z RWY 19

RUTLAND/SOUTHERN VERMONT RGNL (RUT)

RNP APCH - GPS


V Circling NA northeast of Rwy 19 and 31. Circling Rwy 13, 31 NA
A at night. Inop table does not apply to LNAV/VNAV all Cts, Baro-
⊗ VDP NA. For inop ALS, do not increase LPV all Cts visibility to 1 $\frac{1}{2}$ miles.
VDP NA when using VSF altimeter setting. For inop ALS while using
VSF altimeter setting, increase LPV all Cts visibility to 1 $\frac{1}{2}$ miles. Inop
table does not apply when using VSF altimeter setting to LNAV/VNAV
all Cts and LNAV Cat C. When local altimeter setting not received,
use VSF altimeter setting and increase LPV DA to 1281 feet and all
visibilities $\frac{1}{2}$ SM; increase LNAV/VNAV DA to 2230 feet; increase all
MDAs 80 feet and LNAV visibility Cat C $\frac{1}{2}$ SM.

MALSR




MISSED APPROACH: Climb to 1500 then climbing right turn to 5700 direct JOGIM and hold, continue climb-in-hold to 5700. Missed approach requires minimum climb of 420 feet per NM to 3200; if unable to meet climb gradient, see RNAV (GPS) Y Rwy 19.

AWOS-3PT 118.375	BOSTON CENTER 135.7 282.2	UNICOM 122.8 (CTAF) 
----------------------------	-------------------------------------	---

[illegible]

CATEGORY		A	B	C	D
LPV	DA †	1201-3 ⁴ / ₄	414 (500-3 ⁴ / ₄)		NA
RNAV/ VNAV	DA	2150-5	1363 (1400-5)		NA
RNAV	MDA †	1820-3 ⁴ / ₄ 1033 (1100-3 ⁴ / ₄)	1820-1 1033 (1100-1)	1820-2 1/2 1033 (1100-2 1/2)	NA
C CIRCLING		2560-1 1/4 1773 (1800-1 1/4)	2560-1 1/2 1773 (1800-1 1/2)	2560-3 1773 (1800-3)	NA

ELEV 787	D	TDZE 787
----------	----------	----------



HIRL Rwy 1-19 **L**
MIRL Rwy 13-31 **L**
REIL Rwy 13 **L**

RNAV (GPS) Z RWY 19