


LOC I-MBL	APP CRS	Rwy Idg	5501
108.35	277°	TDZE	621
		Apt Elev	621


ILS or LOC RWY 28
MANISTEE COUNTY/BLACKER (MBL)


ADF required for missed approach. RADAR required for procedure entry. DME or RADAR required.	MALSR	MISSED APPROACH: Climb to 2000 then climbing right turn to 2500 direct JEPOT LOM/MBL 4.8 DME and hold.
⚠ ⚠ Circling Rwy 1, 19 NA at night. For inop ALS, increase FATEV fix minimums S-LOC 28 Cat C and D visibility to 1 SM. DME from MBL DME. DME use requires simultaneous reception of I-MBL and MBL DME.	⚠ ⚠	

AWOS-3PT 118.825	MINNEAPOLIS CENTER 120.85 322.35	UNICOM 122.8 (CTAF) ⓪
---------------------	-------------------------------------	--------------------------



ELEV 621	D	TDZE 621
----------	---	----------



2000	2500	MB LOM	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 45).		JANUP MBL 12 RADAR
			MB LOM JEPOT MBL 4.8		
					
CATEGORY	A		B	C	D
S-ILS 28	821-½ 200 (200-½)				
S-LOC 28	1160-½	539 (600-½)	1160-1	539 (600-1)	
 CIRCLING	1160-1 539 (600-1)	1220-1 599 (600-1)	1400-2¼ 779 (800-2¼)	1520-3 899 (900-3)	
FATEV FIX MINIMUMS					
S-LOC 28	1000-½	379 (400-½)	1000-5⁄8	379 (400-5⁄8)	
 CIRCLING	1160-1 539 (600-1)	1220-1 599 (600-1)	1400-2 ¼ 779 (800-2¼)	1520-3 899 (900-3)	

EC-1, 17 APR 2025 to 15 MAY 2025

EC-1, 17 APR 2025 to 15 MAY 2025