

APP CRS	Rwy Idg	9000
267°	TDZE	96
	Apt Elev	96

RNAV (RNP) Y RWY 26R
GEORGE BUSH INTCNL/HOUSTON (IAH)

⚠ For uncompensated Baro-VNAV systems, procedure NA below -3°C (27°F) or above 54°C (130°F). GPS required. Simultaneous approach authorized. For inop ALS, increase RNP 0.11 all Cnts visibility to RVR 5000 and increase RNP 0.15 all Cnts visibility to 1½ SM. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

ALS-F-2

MISSED APPROACH: Climb to 600 then climbing right turn to 3000 direct PEPBI and hold.

D-ATIS	HOUSTON APP CON	HOUSTON TOWER	GND CON	CLNC DEL	CPDLC
124.05	120.05 379.1 EAST 124.35 316.15 WEST	120.72 290.2	121.7	128.1	

RADAR REQUIRED

4 NM

PEPBI

2049

5100 087° (3)

SKLER (IF) 6000 210K (RF REQD)

DRKAR

2600 to SOOPR (8.1)

SOOPR

3000 267° (7.2)

CHUBS

2600 to SOOPR 267° (1.8)

2000 267° (2.6)

OWELL

267°

255

258±

399

256

530

646

5000 235° (3)

4000 267° (4.2)

5000 267° (5)

NEWLY 5000

RAIDS (IF)

GRIZL

6000 200° (3.2)

HOOTI (IAF) 6000 210K

ZAPPO (IAF)

MSA RW26R 2.5 NM

3100

ELEV	96	TDZE	96
------	----	------	----

267°

9000 X 1.50

9402 X 1.50

TWR 422

10000 X 1.50

1000 X 1.50

331

33R

27

600	3000	PEPBI	See planview for multiple IF locations.
-----	------	-------	---

RW26R

OWELL

SOOPR

2000

267°

2600

2000

GP 3.00°

TCH 59

5.8 NM

2.6 NM

CATEGORY	A	B	C	D
RNP 0.11 DA		429/40	333 (400-¾)	
RNP 0.15 DA		496/45	400 (400-¾)	
RNP 0.30 DA		554/50	458 (500-1½)	

AUTHORIZATION REQUIRED