RNAV (GPS) RWY 18

FLETCHER FLD (CKM)

WAAS CH 72619 W18A	APP CRS 183°	Rwy Idg 5404 TDZE 173 Apt Elev 173

RNP APCH-GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Baro-VNAV and VDP NA when using Tunica altimeter setting. When local altimeter setting not received, use Tunica altimeter setting: increase LPV DA to 483 feet, LNAV/VNAV DA to 647 feet and all MDA 60 feet; increase LPV all Cats visibility ⅛ SM, LNAV/VNAV all Cats visibility ¼ SM, and LNAV Cat C/D visibility ⅛ SM. Circling Rwy 36 NA at night.

MISSED APPROACH: Climb to 2000 direct HULON and hold.

AWOS-3	MEMPHIS CENTER	UNICOM
120.675	135.3 335.8	122.8 (CTAF) L







CATEGORY	A	B	C	D
LPV DA	423-⅞ 250 (300-⅞)			
LNAV/VNAV DA	587-1⅜ 414 (500-1⅜)			
LNAV MDA	640-1 467 (500-1)		640-1⅜ 467 (500-1⅜)	
C CIRCLING	740-1 567 (600-1)		780-1¾ 607 (700-1¾)	780-2 607 (700-2)

REIL Rwys 18 and 36 L
MIRL Rwy 18-36 L

SC-4, 17 APR 2025 to 15 MAY 2025
SC-4, 17 APR 2025 to 15 MAY 2025