


WAAS CH 49135 W04A	APP CRS 040°	Rwy Idg 5002 TDZE 181 Apt Elev 182
--	------------------------	---

RNAV (GPS) RWY 4
DEXTER B FLORENCE MEML FLD (ADF)

NA DME/DME RNP-0.3 NA. When local altimeter setting not received use Hot Springs altimeter setting and increase all DA 103 feet and MDA 120 feet and increase LPV all Cats visibility $\frac{1}{8}$ mile and LNAV/VNAV all Cats visibility and Circling Cat C visibility $\frac{1}{2}$ mile. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Baro-VNAV NA when using Hot Springs altimeter setting. Helicopter visibility reduction below $\frac{3}{4}$ SM NA. Night landing: Rwy 22 NA.

MISSED APPROACH:
Climb to 2100 direct
COVNO and hold.

AWOS-3PT 118.175	MEMPHIS CENTER 128.475 377.15	UNICOM 122.7 (CTAF) 0
----------------------------	---	---------------------------------



4 NM Holding Pattern

CUBUG

FITIL

2000

WIPTI 3.1 NM to RW04

RW04

2000

GP 3.00° TCH 45

*1200

VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 23).

2100

COVNO

*LNAV only.

CATEGORY	A	B	C	D
LPV DA	431-1	250 (300-1)		NA
LNAV/VNAV DA	669-1 ⁵ / ₈	488 (500-1 ⁵ / ₈)		NA
LNAV MDA	680-1	499 (500-1)	680-1 ³ / ₈ 499 (500-1 ³ / ₈)	NA
CIRCLING	760-1 578 (600-1)	800-1 618 (700-1)	1040-2 ¹ / ₂ 858 (900-2 ¹ / ₂)	NA

MIRL Rwy 4-22

REIL Rws 4 and 22

RNAV (GPS) RWY 4