

WAAS CH 48940	APP CRS 129°	Rwy Idg TDZE 54
W13A		Apt Elev 55

RNAV (GPS) RWY 13

KNOX COUNTY RGNL (RKD)

▼



DME/DME RNP -0.3 NA. VDP and Baro-VNAV NA when using Wiscasset altimeter setting. When local altimeter setting not received, use Wiscasset altimeter setting and increase LPV DA to 319 feet, LNAV/VNAV DA to 467 feet and all MDA 80 feet. Increase LNAV/VNAV visibility all Cats to 1 SM, LNAV Cat C/D to 1 SM and Circling Cat C to 2 ¼ SM. For inop ALS increase LNAV/VNAV all Cats visibility to 1 ½ SM. For inop ALS when using Wiscasset altimeter setting increase LPV all Cats visibility to ¾ SM, LNAV/VNAV all Cats visibility to 1 ¾ SM and LNAV Cat C/D to 1 ¾ SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F).

MALSR

MISSED APPROACH:

Climb to 800 then climbing right turn to 2400 direct AVMAW and hold.

AWOS-3PT 119.025	PORTLAND APP CON ★ 120.4 299.2	CLNC DEL 123.8	UNICOM 123.05 (CTAF) 0
----------------------------	--	--------------------------	----------------------------------



ELEV 55

D

TDZE 54

800

2400

AVMAW

*LNAV only

REIL Rwy 3 and 31 0

MIRL Rwy 3-21 0

HIRL Rwy 13-31 0

4000 X 100

5412 X 100