

TOP ALTITUDE:
ASSIGNED BY ATC

DETROIT DEP CON
132.35 284.0
ATIS
125.025
CLNC DEL
118.25
GND CON
121.9
PONTIAC TOWER★
120.5 (CTAF)

RNAV-1 DME/DME/IRU or GPS.
RADAR required.

NAV-1 DME/DME/IRU or GPS.
RADAR required.

N

← 275° ———→ 095°

TAKEOFF RUNWAYS 9L/R: Climb on heading 095° or as assigned by ATC, thence....
TAKEOFF RUNWAYS 27L/R: Climb on heading 275° or as assigned by ATC, thence....
.....for RADAR vectors to JWELS, then on track 218° to SNDRS, then on (transition). Maintain ATC assigned altitude, expect filed altitude 10 minutes after departure.
BGHRT TRANSITION (SNDRS3.BGHRT):
TORRR TRANSITION (SNDRS3.TORRR):

NOTE: Turbojet departures at/above 10000, maintain 280K until advised by ATC.
NOTE: TORRR Transition: For use by KIND and KCVG area arrivals only and flights filed at or below FL220, or as assigned by ATC.

JWELS
218°
(31)
275°
(24)
SNDRS
8000
*2400
255°
(24)
REEDA
8000
*2400
265°
(30)
SEABS
8000
*2200
264°
(28)
KNRKO
8000
*2400
269°
(94)
BGHRT
TORRR
209°
(33)
2400
8000

TAKEOFF MINIMUMS:
Rwys 18, 36: NA - Environmental.
Rwys 9L/R, 27L/R: Standard.

NASA PTK 25 NM
2900

NOTE: Chart not to scale.

EC-1, 12 JUN 2025 to 10 JUL 2025

SNDRS THREE DEPARTURE (RNAV)

(SNDRS3.SNDRS) 16MAY24

PONTIAC, MICHIGAN
OAKLAND COUNTY INTL (PTK)