


WAAS CH 70711 W34A	APP CRS 340°	Rwy Idg 7100 TDZE 1232 Apt Elev 1232
--	------------------------	---

RNAV (GPS) RWY 34

BRainerd Lakes RGNL (BRD)

RNP APCH - GPS.	MALSR	MISSED APPROACH: Climb to 3300 direct KRINK and on 294° track to CUCAC and hold.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. Baro-VNAV and VDP NA when using AIT altimeter setting. When local altimeter setting not received, use AIT altimeter setting and increase LPV DA to 1484 feet; increase LNAV/VNAV DA to 1578 feet and all visibilities ½ SM. Increase all MDAs 60 feet and LNAV visibility Cat C/D ¼ SM. For inop ALS when using AIT altimeter setting, increase LNAV/VNAV all Cats visibility to 1 SM. For inop ALS increase LNAV/VNAV all Cats visibility to ¾ SM.		

ASOS 126.775	MINNEAPOLIS CENTER 118.05 239.0	UNICOM 122.7 (CTAF)
------------------------	---	-------------------------------



3300	KRINK	tr 294°	CUCAC
UXOWO 1.7 NM to RW34			
1.1 NM to RW34			
RW34			
1820			
3000			
OSHA 4 NM Holding Pattern			
160° → 6000			
← 340° 3000			
GP 3.00° TCH 47			
1.1 NM 0.6 NM 3.7 NM 6.1 NM			
CATEGORY	A	B	C
LPV DA	1432-½		200 (200-½)
LNAV/VNAV DA	1526-½		294 (300-½)
LNAV MDA	1620-½	388 (400-½)	1620-⅝ 388 (400-⅝)
CIRCLING	1760-1	528 (600-1)	1760-1½ 528 (600-1½) 1840-2 608 (700-2)

