

WAAS CH 45632 W24A	APP CRS 240°	Rwy Idg TDZE 2573 Apt Elev 2573
--	------------------------	---

RNAV (GPS) RWY 24

BIG SPRING/MC MAHON-WRINKLE (BPG)

RNP APCH.


▼

▲


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. When local altimeter setting not received, use Midland Intl Air and Space Port altimeter setting: increase all DA 130 feet and all MDA 140 feet; increase LPV and LNAV/VNAV Cats A/B visibility ½ SM, and LNAV Cat A visibility ¼ SM. Baro-VNAV and VDP NA with Midland Intl Air and Space Port altimeter setting. Rwy 24 helicopter visibility reduction below ¾ SM NA.


MISSED APPROACH: Climb to 4600 direct ZIVGU and hold.

AWOS-3PT 118.025	FORT WORTH CENTER 133.7 350.2	UNICOM 122.8 (CTAF) 0
----------------------------	---	---------------------------------



ELEV 2573	TDZE 2573
-----------	-----------



4600	ZIVGU	VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 40).			
		5 NM Holding Pattern			
*LNAV only.					
					
CATEGORY	A	B	C	D	
LPV DA	2823-¾	250 (300-¾)	NA		
LNAV/ VNAV DA	3236-2¼	663 (700-2¼)	NA		
LNAV MDA	3380-1 807 (900-1)	3380-1¼ 807 (900-1¼)	NA		

SC-2, 27 NOV 2025 to 25 DEC 2025

SC-2, 27 NOV 2025 to 25 DEC 2025