

WAAS CH 56419 W35A	APP CRS 353°	Rwy Idg TDZE Apt Elev	6099 1238 1258
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 35


FREDERICK RGNL (FDR)

RNP APCH-GPS.


⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 46°C .
⚠ Baro-VNAV and VDP NA when using Vernon altimeter setting. When local altimeter setting not received, use Vernon altimeter setting: increase LPV DA to 1478 feet; increase LNAV/VNAV DA to 1540 feet; increase all MDAs 40 feet and visibility LNAV Cat C ¼ SM and Circling Cat D ½ SM. Circling Rwy 3, 12,17, 21, 30, NA at night.

MISSED APPROACH: Climb to 4000 direct JIVUG and right turn on track 083° to HUNBI and right turn on track 173° to HUNTEX and right turn on track 263° to FAWCI and hold.

ASOS 132.675	ALTUS APP CON ★ 125.1 353.7	UNICOM 123.05 (CTAF) 0
------------------------	---------------------------------------	----------------------------------



ELEV 1258	TDZE 1238
-----------	-----------



4000	JIVUG	HUNBI	HOTEX	FAWCI
↑	tr 083°	tr 173°	tr 263°	
4 NM Holding Pattern				
FAWCI				
173° → 4000				
← 353°				
GP 3.00° TCH 40				
1 NM 1.4 NM 2.6 NM 6 NM				
CATEGORY	A	B	C	D
LPV DA	1438-¾ 200 (200-¾)			
LNAV/VNAV DA	1500-1 262 (300-1)			
LNAV MDA	1600-1 362 (400-1)			1600-1¼ 362 (400-1¼)
CIRCLING	1700-1 442 (500-1)	1720-1 462 (500-1)	1880-1¾ 622 (700-1¾)	1900-2 642 (700-2)

SC-1, 27 NOV 2025 to 25 DEC 2025

SC-1, 27 NOV 2025 to 25 DEC 2025