

WAAS CH 50530 W29B	APP CRS 292°	Rwy Ldg TDZE Apt Elev	8008 331 336
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 29L


FRESNO YOSEMITE INTL (FAT)

▼


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 0°C (32°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 2000 direct WOSIM and hold.

ATIS 121.35 273.6	FRESNO APP CON 119.6 351.95	FRESNO TOWER 118.2 251.1	GND CON 121.7 348.6	CLNC DEL 124.35 348.6
-----------------------------	---------------------------------------	------------------------------------	-------------------------------	---------------------------------



ELEV 336	D	TDZE 331
----------	----------	----------



2000	WOSIM	4 NM Holding Pattern			
*LNAV only.		CUMUX 1.4 NM to RW29L	ZUDAB 1800	IPUJE	GP 3.00° TCH 52
RW29L		*820	1800	292°	112°
		1.4 NM	3.1 NM	6.4 NM	
CATEGORY	A	B	C	D	
LPV DA	581-¾ 250 (300-¾)				
LNAV/VNAV DA	667-1⅛ 336 (400-1⅛)				
LNAV MDA	760-1	429 (500-1)	760-1¼	429 (500-1¼)	
CIRCLING	820-1	484 (500-1)	920-1½	920-2	
			584 (600-1½)	584 (600-2)	