

APP CRS
271°

Rwy Ldg
TDZE
3852

Apt Elev
3877

RNAV (RNP) Z RWY 27
HELENA RGNL (HLN)

RNP AR APCH - GPS.

▼

▲

❄

Inop table does not apply to RNP 0.30 DA. For uncompensated Baro-VNAV systems, procedure NA below -28°C or above 54°C. For inop ALS, increase RNP 0.13 DA* visibility all Cats to ¾ SM, RNP 0.30 DA* visibility all Cats to 1¾ SM.

MALSR

AS

MISSED APPROACH:

Climb to 12000 on the RNAV missed approach route to PIXXI and hold, continue climb-in-hold to 12000.

*Missed approach requires minimum climb of 280 feet per NM to 7800.

#Missed approach requires minimum climb of 375 feet per NM to 6300.

ATIS 120.4	HELENA APP CON * 119.5 229.4	HELENA TOWER * 118.3 (CTAF) 0 257.8	GND CON 121.9	UNICOM 122.95
---------------	---------------------------------	--	------------------	------------------

ELEV 3877	D	TDZE 3852		
See planview for multiple IF locations.				
CATEGORY	A	B	C	D
RNP 0.13 DA*		4172-½	320 (300-½)	
RNP 0.20 DA#		4303-⅞	451 (500-⅞)	
RNP 0.30 DA#		4353-1	501 (500-1)	
RNP 0.30 DA		4866-4	1014 (1000-4)	
AUTHORIZATION REQUIRED				

HELENA, MONTANA
Amdt 2 25JAN24

46°36'N-111°59'W

HELENA RGNL (HLN)
RNAV (RNP) Z RWY 27