

LOC/DME I-FVJ 111.15 Chan 48 (Y)	APP CRS 230°	Rwy Ldg 10000 TDZE 790 Apt Elev 796
--	------------------------	--

ILS or LOC RWY 23L
INDIANAPOLIS INTL (IND)

T Simultaneous approach authorized.
A * RVR 1800 authorized with use of FD or AP or HUD to DA.



MISSED APPROACH: Climb to 1500 then climbing left turn to 3000 on heading 100° and on VHP VORTAC R-136 to OZMOE INT/VHP 20.1 DME and hold.

D-ATIS 134.25	INDIANAPOLIS APP CON 128.175 317.8	INDY TOWER 120.9 251.1	GND CON 121.9	CLNC DEL 128.75 251.1	CPDLC
------------------	---------------------------------------	---------------------------	------------------	--------------------------	-------




Diagram illustrating the VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 71).

Key parameters and distances shown:

- 1 NM
- 4.5 NM
- 4.4 NM
- 3.1 NM
- Altitudes: 2600, 4000, 5000
- Angles: 230°, 4000, 5000
- GS 3.00° TCH 55

CATEGORY	A	B	C	D
S-ILS 23L *	990/24		200 (200-½)	
S-LOC 23L	1180/24	390 (400-½)	1180/35	390 (400-⅝)
CIRCLING	1420-1	624 (700-1)	1420-1¾ 624 (700-1¾)	1560-2½ 764 (800-2½)

