

APP CRS 320°	Rwy Ldg	7278
	TDZE	793
	Apt Elev	796

RNAV (RNP) Z RWY 32

INDIANAPOLIS INTL (IND)

For uncompensated Baro-VNAV systems, procedure NA below -18°C (2°F) or above 54°C (130°F). GPS required.

MALSR

MISSED APPROACH: Climb to 3000 on track 320° to KEADY and hold.

D-ATIS 134.25	INDIANAPOLIS APP CON 128.175 317.8	INDY TOWER 120.9 251.1	GND CON 121.9	CLNC DEL 128.75 251.1	CPDLC
------------------	---------------------------------------	---------------------------	------------------	--------------------------	-------

The main chart displays the RNP Z RWY 32 procedure. Key features include:

- Initial Approach:** (IF) CRCL 6000 210K (RF REQD) at 4400 ft, 140° heading, 15.3 NM from RW32.
- Intermediate Approach:** (IF) HNKLE 5000 210K (RF REQD) at 3600 ft, 205° heading, 4.2 NM from CUREG.
- Final Approach:** (FAF) BTTLR at 2400 ft, 320° heading, 4.9 NM from RW32.
- Obstacles:** HIKEK (3600 ft, 2.9 NM), EVAVE (200K, 4.2 NM), BDAWG (5000 ft, 4.2 NM), and OZMOE (4500 ft, 210K).
- Missed Approach:** Climb to 3000 ft on track 320° to KEADY and hold. A diagram shows the missed approach fix (MISSED APCH FIX) at 4 NM from KEADY, with a 139° heading and 319° turn.
- MSA:** Minimum Safe Altitude for RW32 is 3100 ft, with a 25 NM radius.
- Navigation Aids:** Various navigation aids are shown, including VORTAC stations and their frequencies.

ELEV 796

D

TDZE 793

Diagram illustrating the RNP Z RWY 32 procedure, showing the glide path, missed approach, and various navigation aids.

3000

KEADY

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 73).

BTTLR

2400

GP 3.00°

TCH 53

See planview for multiple IF locations.

4.9 NM

See planview for multiple IF locations.

CATEGORY	A	B	C	D
RNP 0.19 DA		1134/30	341 (400-%)	
RNP 0.30 DA		1196/45	403 (400-%)	

AUTHORIZATION REQUIRED

INDIANAPOLIS, INDIANA

Amdt 2 10NOV16

39°43'N-86°18'W

INDIANAPOLIS INTL (IND)

RNAV (RNP) Z RWY 32