

WAAS CH 86509 W36A	APP CRS 360°	Rwy Ldg 7433 TDZE 653 Apt Elev 656
--	------------------------	---

RNAV (GPS) RWY 36

LA CROSSE RGNL (LSE)

RNP APCH.

 For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -27° C or above 54° C. When local altimeter setting not received, use Winona altimeter setting: increase LPV DA to 1006 feet, LNAV/VNAV DA to 1256 feet and all MDA 60 feet. Increase LPV all Cats visibility ¼ SM, LNAV/VNAV all Cats visibility ¼ SM, LNAV Cats C/D visibility ¼ SM and Circling Cat C visibility ¼ SM. Circling to Rwy 22 NA at night. Baro-VNAV and VDP NA when using Winona altimeter setting.

MISSED APPROACH:
Climb to 3500 direct
POGOC and hold.

ATIS 124.95	MINNEAPOLIS CENTER 128.6 363.0	LA CROSSE TOWER ★ 118.45 (CTAF) 0 251.075	GND CON 121.8	UNICOM 122.95
-----------------------	--	---	-------------------------	-------------------------

NoPT for arrival on V129
northwest bound.

RW36

(FAF)
C|VM|

(8)

(IF/IAF

 $\pm 4 \text{ NM}$

MISSED APCH FIX

4 NM
Holding Pattern

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 28)

3500	POGOC
------	-------

$$\frac{3000}{36} \leftarrow 18$$

GP 3.00°
TCH 50

2500'

*1.5.114

*LNAV only.

RW36 

CATEGORY	A	B	C	D
LPV DA	953-1 300 (300-1)			
LNAV/ VNAV DA	1203-2 550 (600-2)			
LNAV MDA	1140-1 487 (500-1)	1140-1¼ 487 (500-1¼)	1140-1½ 487 (500-1½)	
CIRCLING	1140-1 484 (500-1)	1460-1 804 (900-1)	1760-3 1104 (1200-3)	1820-3 1164 (1200-3)

LA CROSSE, WISCONSIN

Orig-D 03JAN19

43°53'N-91°15'W

LA CROSSE RGNL (LSE)

RNAV (GPS) RWY 36