

APP CRS	Rwy Ldg	8926
251°	TDZE	122
	Apt Elev	128

RNAV (RNP) Z RWY 24R

LOS ANGELES INTL (LAX)

RNP AR APCH-GPS.

▼

Simultaneous approach authorized with HHR. For uncompensated Baro-VNAV systems, procedure NA below 5°C or above 54°C. For inop ALS, increase RNP 0.15 all Cats visibility to RVR 6000 and RNP 0.30 all Cats visibility to 1½ SM. Simultaneous approach authorized.


ALSIF-2

ⓘ




ⓐ

MISSED APPROACH: Climb to 2000 on track 251° to IGUPE and track 263° to RAFFS and hold.

D-ATIS	SOCAL APP CON	LOS ANGELES TOWER	GND CON
133.8	124.3 363.2 (APCH from W) 124.9 269.0 (090°-224°) 124.5 235.975 (225°-044°) 128.5 360.7 (045°-089°)	133.9 239.3 (N) 120.95 379.1 (S)	121.65 327.0 (N) 121.75 327.0 (S) 121.4 327.0 (W)



ELEV 128	D	TDZE 122
----------	----------	----------



CATEGORY	A	B	C	D
RNP 0.15 DA	484/40	362 (400-¾)		
RNP 0.30 DA	586/60	464 (500-1½)		