

VORTAC MRB

112.1

Chan 58

APP CRS

290°

Rwy Ldg TDZE

N/A

Apt Elev

N/A

N/A

N/A

565

VOR-A


EASTERN WV RGNL/SHEPHERD FLD (MRB)

RADAR required for procedure entry at HARPP.

When local altimeter setting not received, use HGR altimeter setting: increase all MDAs 80 feet and Circling visibility Cats C/D ¼ SM.

MISSED APPROACH: Climbing left turn to 3000 direct MRB VORTAC and hold, continue climb in hold to 3000.

ASOS 119.925	POTOMAC APP CON 126.825 239.025	MARTINSBURG TOWER★ 124.3 (CTAF) 233.7	GND CON 121.8 257.65	UNICOM 122.95
-----------------	------------------------------------	--	-------------------------	------------------



3000 MRB

MRB VORTAC

One Minute Holding Pattern

110° 6000 3000

290°

5.7 NM

TWR

8815 X 150

290°

REIL Rwy 8

HIRL Rwy 8-26

CATEGORY	A	B	C	D	E	FAF to MAP 5.7 NM				
CIRCLING	1120-1 555 (600-1)	1240-1 675 (700-1)	1240-2 675 (700-2)	1320-2½ 755 (800-2½)	2180-3 1615 (1700-3)	Knots	60	90	120	150
						Min:Sec	5:42	3:48	2:51	2:17
										1:54