

WAAS CH 42600 W04A	APP CRS 043°	Rwy Ldg 5764 TDZE 2634 Apt Elev 2634
--	------------------------	---

RNAV (GPS) RWY 4



FRANK WILEY FLD (MLS)

RNP APCH-GPS.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -25°C or above 54°C. When local altimeter setting not received, use Glendive altimeter setting: increase LPV and LNAV/VNAV DA to 3051 and all visibilities ½ SM. Increase all MDA 180 feet and LNAV Cat C and D visibilities ¾ SM and Circling Cat C and D visibilities ½ SM. Baro-VNAV and VDP NA when using Glendive altimeter setting.

MISSED APPROACH: Climb to 6000 direct AXUPE and hold, continue climb-in-hold to 6000.

ASOS 135.575	SALT LAKE CENTER 126.85 305.2	UNICOM 123.0 (CTAF) 0
------------------------	---	---------------------------------



CATEGORY		A	B	C	D
LPV	DA	2884-1		250 (300-1)	
LNAV/ VNAV	DA	2884-1		250 (300-1)	
LNAV	MDA	3040-1	406 (500-1)	3040-1½	406 (500-1½)
CIRCLING		3060-1 426 (500-1)	3100-1 466 (500-1)	3160-1½ 526 (600-1½)	3320-2¼ 686 (700-2¼)

