

WAAS CH 70729 W07A	APP CRS 073°	Rwy Ldg TDZE 109 Apt Elev 113
--	------------------------	---

RNAV (GPS) RWY 7

ORLANDO EXEC (ORL)

RNP APCH-GPS.

⚠

Circling Rwy 31 NA at night. Rwy 7 helicopter visibility reduction below ¾ SM NA.

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 2°C or above 54°C.


⚠

For inop ALS, increase LPV all Cats visibility to RVR 4500, increase LNAV/VNAV all Cats visibility to RVR 5000, increase LNAV Cat A/B visibility to RVR 5500 and Cats C/D to 1¾ SM. In minimum visibility conditions, bright lights on highway ½ mile south of airport may be mistaken for runway lights.

MALSR

MISSED APPROACH:
Climb to 1500 direct MSHEL, cross MSHEL at 1500, then climb to 1600 on track 039° to OVIDO and hold.

ATIS 127.25	ORLANDO APP CON 119.4 351.9 (7) 125.225 351.9 (25)	EXECUTIVE TOWER ★ 118.7 (CTAF) 0 239.0	GND CON 121.4 239.0	UNICOM 122.95
-----------------------	--	---	-------------------------------	-------------------------



ELEV 113

TDZE 109

4 NM Holding Pattern

ESRAQ

DNMOR

1500

MSHEL 1500

1600

OVIDO

SWLTR 2.8 NM to RWY 07

1020

1.9 NM to RWY 07

RWY 07

GP 3.00° TCH 52

6.2 NM

3 NM

0.9

1.9

CATEGORY	A	B	C	D
LPV DA	391/40 282 (300-¾)			
LNAV/VNAV DA	447/40 338 (400-¾)			
LNAV MDA	740/40	631 (700-¾)	740-1⅜	631 (700-1⅜)
CIRCLING	740-1	627 (700-1)	860-2¼	860-2½
			747 (800-2¼)	747 (800-2½)

REIL Rwy 13 and 31

HIRL Rwy 7-25 and 13-31