

WAAS CH 40023 W09A	APP CRS 087°	Rwy Ldg 12000 TDZE 21 Apt Elev 36
--	------------------------	--

RNAV (GPS) Y RWY 9R
PHILADELPHIA INTL (PHL)


T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C (11°F) or above 54°C (130°F). DME/DME RNP-0.3 NA.

A For inop ALS, increase LNAV/VNAV visibility all Cats to RVR 5000 and LNAV Cats C/D visibility to RVR 6000.


ALSF-2

MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 direct OOD VORTAC and hold.

D-ATIS 133.4	PHILADELPHIA APP CON 124.35 319.15	PHILADELPHIA TOWER 118.5 327.05 (08/26, 09L/27R, 17/35) 135.1 327.05 (09R/27L)	GND CON 121.9 348.6
-----------------	---------------------------------------	--	------------------------



ELEV 36	D	TDZE 21
---------	----------	---------



CATEGORY		A	B	C	D
LPV	DA	221/18		200 (200-½)	
INAV/ VNAV	DA	346/30		325 (400-¾)	
INAV	MDA	440/24 419 (500-½)		440/40 419 (500-¾)	
CIRCLING		540-1 504 (600-1)	640-1 604 (700-1)	640-1¾ 604 (700-1¾)	720-2¼ 684 (700-2¼)

TDZ/CL Rwy 9R
HIRL all Rwys
REIL Rwys 9L and 35