




Rwy 3:	Standard with minimum climb of 375'	per NM to 5300.
Rwy 10L:	Standard with minimum climb of 350'	per NM to 5900.
Rwy 10R:	Standard with minimum climb of 400'	per NM to 5000.
Rwy 21:	Standard with minimum climb of 430'	per NM to 4000.
Rwy 28L:	Standard with minimum climb of 375'	per NM to 4500.
Rwy 28R:	Standard with minimum climb of 340'	per NM to 5400.

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

▼

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 3: Climb heading 029° to 600, thence. . . .

TAKEOFF RUNWAY 10L: Climb heading 103° to 500, thence. . . .

TAKEOFF RUNWAY 10R: Climb heading 103° to 500, thence. . . .

TAKEOFF RUNWAY 21: Climb heading 209° to 500, thence. . . .

TAKEOFF RUNWAY 28L: Climb heading 283° to 800, thence. . . .

TAKEOFF RUNWAY 28R: Climb heading 283° to 800, thence. . . .

. . . . climb on assigned heading for RADAR vectors to assigned route/fix.

Maintain assigned altitude, expect filed altitude five minutes after departure.

LOST COMMUNICATIONS: If no contact with ATC within 10 NM of airport,

continue climb to assigned altitude and proceed direct BTG VORTAC. Climb in

BTG VORTAC holding pattern to cross BTG VORTAC at or above MCA/MEA before

proceeding on course.

NW-1, 27 NOV 2025 to 25 DEC 2025

NW-1, 27 NOV 2025 to 25 DEC 2025