



WAAS CH 45601 W04A	APP CRS 041°	Rwy Ldg 11301 TDZE 81 Apt Elev 98
--	------------------------	--

RNAV (GPS) RWY 4R
SACRAMENTO MATHER (MHR)

RNP APCH - GPS.	MISSED APPROACH: Climb to 3300 direct STNGR and hold. *Missed approach requires minimum climb of 210 feet per NM to 2500.
Circling NA northwest of Rwy 4R-22L. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.	

ATIS 118.325	NORCAL APP CON 127.4 317.5	MATHER TOWER ★ 120.65(CTAF) 0 282.25	GND CON 121.85 307.9	UNICOM 122.95
------------------------	--------------------------------------	--	--------------------------------	-------------------------



CATEGORY	A	B	C	D
LPV DA*	331/40	250 (300-¾)		
LNAV/VNAV DA*	365/45	284 (300-⅞)		
LNAV MDA*	520/55	439 (500-1)	520-1¼	439 (500-1¼)
LNAV MDA	540/55 459 (500-1)	560/55 479 (500-1)	580-1⅓	499 (500-1⅓)
CIRCLING	560-1 462 (500-1)	580-1 482 (500-1)	600-1½ 502 (600-1½)	740-2 642 (700-2)

