



VORTAC SJT	APP CRS	Rwy Ldg	5940
115.1	045°	TDZE	1917
Chan 98		Apt Elev	1919

VOR Y or TACAN Y RWY 3
SAN ANGELO RGNL/MATHIS FLD (SJT)

DME required.	MALSR	MISSED APPROACH: Climbing left turn to 4400 on SJT VORTAC R-284 to TANKR INT/11 DME and hold, continue climb-in-hold to 4400.
▼ Inop table does not apply to Cat A and B. ⚠ Circling NA for Cat E west of Rwy 18-36. For inop ALS, increase Cat C-E visibility to 2 SM.		

ATIS 128.45 319.0	SAN ANGELO APP CON ★ 125.35 354.1	MATHIS TOWER ★ 118.3 (CTAF) 0 284.7	GND CON 121.9 348.6	UNICOM 122.95
----------------------	--------------------------------------	--	------------------------	------------------



	NIYGO SJT [15]	ILRUH SJT [8.4]	SJT [4.8]	CRTLA SJT [3.3]	4400 SJT R-284 TANKR
	4000	3800	3000	2700	
	045°	3.06° TCH 50	1.5	0.5	
	6.6 NM	3.6 NM	1.5	0.5	
CATEGORY	A	B	C	D	E
S-3	2620/50	703 (800-1)	2620-1½	703 (800-1½)	
CIRCLING	2620-1	701 (800-1)	2620-2 701 (800-2)	2700-2½ 781 (800-2½)	2700-2¾ 781 (800-2¾)