

WAAS CH 48803 W28A	APP CRS 284°	Rwy Ldg 11236 TDZE 13 Apt Elev 13
--	------------------------	--

RNAV (GPS) Z RWY 28R

SAN FRANCISCO INTL (SFO)

RNP APCH - GPS.

▼


▲

Circling N/A to Rwy's 10L, 10R, 19L, and 19R. Circling Rwy 1L, 1R NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 4°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to 1 1/2 SM, increase LNAV Cat C/D visibility to 2 SM.


ALSF-2

MISSED APPROACH: Climb to 3000 direct VIKYU and hold.
*Missed approach requires minimum climb of 350 feet per NM to 1900; if unable to meet climb gradient, see RNAV (GPS) RWY 28L.

D-ATIS 113.7 115.8 118.85	NORCAL APP CON 134.5 338.2	SAN FRANCISCO TOWER 120.5 269.1	GND CON 121.8	CLNC DEL 118.2	CPDLC
---	--------------------------------------	---	-------------------------	--------------------------	-------



ELEV 13	D	TDZE 13
---------	----------	---------



3000 VIKYU VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 68).			
CEPIN			
AXMUL			
2.1 NM to RWY 28R			
RWY 28R			
2.1 NM 3.3 NM 4.6 NM			
GP 3.00° TCH 55			
CATEGORY	A	B	C
LPV DA*	213/18		
LNAV/VNAV DA	642-1 3/8 629 (700-1 3/8)		
LNAV MDA	760/24 747 (800-1/2)	760/40 747 (800-3/4)	760-1 3/4 747 (800-1 3/4)
CIRCLING	760-1 747 (800-1)	1020-1 1/2 1007 (1100-1 1/2)	1640-3 1627 (1700-3)