



WAAS CH 45515 W01A	APP CRS 006°	Rwy Ldg 7002 TDZE 39 Apt Elev 50
--	------------------------	---

RNAV (GPS) RWY 1
SAVANNAH/HILTON HEAD INTL (SAV)

RNP APCH. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C (5°F) or above 49°C (120°F).		MISSED APPROACH: Climb to 2500 direct SUTME and hold.		
ATIS 123.75	SAVANNAH APP CON★ 125.3 371.875	SAVANNAH TOWER★ 125.975 (CTAF) 0 257.8	GND CON 121.9 348.6	UNICOM 122.95



2500	SUTME	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 74).		
*LNAV only.		MIZLU	TERBE	4 NM Holding Pattern
*1.3 NM to RW01		2000	186°	2500
1.3 NM		4.6 NM	006°	GP 3.00° TCH 57
6.3 NM				
CATEGORY	A	B	C	D
LPV DA	239/40 200 (200-¾)			
LNAV/VNAV DA	384/60 345 (400-1¼)			
LNAV MDA	520/55	481 (500-1)	520-1⅓	481 (500-1⅓)
CIRCLING	520-1	470 (500-1)	740-2 690 (700-2)	740-2¼ 690 (700-2¼)

SE-4, 27 NOV 2025 to 25 DEC 2025

SE-4, 27 NOV 2025 to 25 DEC 2025