

WAAS
CH **45606**
W23A

APP CRS
238°

Rwy Ldg
TDZE
Apt Elev
8002
3967
3967

SCOTTSBLUFF/WESTERN NEBRASKA RGNL/WM B HEILIG FLD (BFF)

RNAV (GPS) RWY 23


When local altimeter setting not received, use Alliance altimeter setting: increase LPV DA to 4347 feet and visibility ¼ SM; increase LNAV/VNAV DA to 4679 feet; increase all MDAs 100 feet and visibility Cats C and D ½ SM. Baro-VNAV NA when using Alliance altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C (-7°F) or above 41°C (105°F). VDP NA when using Alliance altimeter setting. Visibility reduction by helicopters NA. DME/DME RNP-0.3 NA.

MISSED APPROACH: Climb to 6700 direct GESBE and via 243° track to PUREE and hold.

ASOS
121.025

DENVER CENTER
127.95 338.2

UNICOM
123.0 (CTAF) 1



ELEV 3967

D

TDZE 3967

6700

GESBE

243° tr

PUREE

LNNAV/VNAV - Fly visual 238° 1.8 NM, when using Alliance altimeter setting fly visual 238° 2.1 NM.

5 NM Holding Pattern

KOBSE

AYANI

5800

6600

058°

238°

GP 3.00° TCH 52

1.3 NM

4.2 NM

6.1 NM

CATEGORY	A	B	C	D
LPV DA	4256-1	289 (300-1)		
LNNAV/VNAV DA	4588-2	621 (700-2)		
LNNAV MDA	4420-1	453 (500-1)	4420-1¼ 453 (500-1¼)	4420-1½ 453 (500-1½)
CIRCLING	4500-1	533 (600-1)	4560-1½ 593 (600-1½)	4740-2½ 773 (800-2½)

HIRL Rwy 12-30 1

MIRL Rwy 5-23 1