



WAAS CH 57911 W13A	APP CRS 133°	Rwy Ldg TDZE 1095 Apt Elev 1098
--	------------------------	---

RNAV (GPS) RWY 13

SIoux GATEWAY/BRIG GENERAL BUD DAY FLD (SU_X)

RNP APCH-GPS. ⚠ Inop table does not apply to LPV all Cats. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. For inop ALS, increase LNAV/VNAV Cat E visibility to 1½ SM and LNAV Cat E visibility to 1½ SM.	MALS ⚠	MISSED APPROACH: Climb to 3900 direct WAVUK and hold.
---	--	---

ATIS 119.45 270.8	SIoux CITY APP CON ★ 124.6 307.0	SIoux CITY TOWER ★ 118.7 (CTAF) 0 254.3	GND CON 121.9 348.6	UNICOM 122.95
-----------------------------	--	---	-------------------------------	-------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 50).					3900 ↑	WAVUK ✦	
4 NM Holding Pattern							
6000 ← 313°							
3500 → 133°							
GP 3.00° TCH 54							
VOGYU							
YABUR							
2500							
2500							
6.8 NM							
2.7 NM							
1.5 NM							
*1.5 NM to RW13							
RW13							
					*LNAV only.		
CATEGORY	A	B	C	D	E		
LPV DA	1295/40 200 (200-¾)						
LNAV/ VNAV DA	1582/60 487 (500-1¼)						
LNAV MDA	1620/40	525 (600-¾)	1620-1¼ 525 (600-1¼)				
CIRCLING	1640-1 542 (600-1)	1700-1 602 (700-1)	1700-1¼ 602 (700-1¼)	1860-2½ 762 (800-2½)	2000-3 902 (1000-3)		