



WAAS CH 53611 W22A	APP CRS 223°	Rwy Ldg 4945 TDZE 23 Apt Elev 24
--	------------------------	---

RNAV (GPS) RWY 22
VERO BEACH RGNL (VRB)

⚠ Circling to Rwy 30R NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 0°C (32°F) or above 43°C (109°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Fort Pierce altimeter setting and increase LPV DA to 363 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 567 feet and all visibilities ½ SM; increase all MDAs 40 feet and LNAV Cat C/D visibility ¼ SM and Circling Cat C/D visibility ¼ SM. Baro-VNAV and VDP NA when using Fort Pierce altimeter setting. Rwy 22 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climb to 2000 direct
JINSO and hold.

ATIS 120.575	PALM BEACH APP CON 123.625 225.4(N)	VERO BEACH TOWER ★ 126.3 (CTAF) 0	GND CON 127.45	UNICOM 122.95
------------------------	---	---	--------------------------	-------------------------



ELEV 24	D	TDZE 23
MIRL Rwy 4-22, 12R-30L, and 12L-30R 0		
REIL Rwy 4, 12R, 22 and 30L 0		
CATEGORY A B C D		
LPV DA 340-1 317 (400-1)		
LNAV/VNAV DA 544-1¾ 521 (600-1¾)		
LNAV MDA 520-1 497 (500-1) 520-1¾ 497 (500-1¾)		
CIRCLING 560-1 536 (600-1) 660-1¾ 820-2½ 636 (700-1¾) 796 (800-2½)		