

|                                        |                        |                                                   |
|----------------------------------------|------------------------|---------------------------------------------------|
| WAAS<br>CH <b>65919</b><br><b>W01A</b> | APP CRS<br><b>007°</b> | Rwy Ldg<br>TDZE <b>511</b><br>Apt Elev <b>516</b> |
|----------------------------------------|------------------------|---------------------------------------------------|

RNAV (GPS) RWY 1

WACO RGNL (ACT)

RNP APCH - GPS.

⚠

ASR

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -8°C or above 54°C. Baro-VNAV and VDP NA when using PWG altimeter setting. Rwy 1 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use PWG altimeter setting and increase LPV DA to 792 feet and all visibilities ½ SM. Increase LNAV/VNAV DA to 813 feet; increase all MDAs 40 feet and LNAV visibility Cat C/D ½ SM, and Circling visibility Cat D ¼ SM.

MISSED APPROACH:  
Climb to 3000 direct  
CHRU and hold.

|                       |                                         |                                             |                         |                         |
|-----------------------|-----------------------------------------|---------------------------------------------|-------------------------|-------------------------|
| ATIS<br><b>123.85</b> | WACO APP CON ★<br><b>127.65 227.125</b> | WACO TOWER ★<br><b>119.3 (CTAF) 0 257.8</b> | GND CON<br><b>121.9</b> | UNICOM<br><b>122.95</b> |
|-----------------------|-----------------------------------------|---------------------------------------------|-------------------------|-------------------------|

