

|                                        |                        |                                                   |
|----------------------------------------|------------------------|---------------------------------------------------|
| WAAS<br>CH <b>69420</b><br><b>W32A</b> | APP CRS<br><b>322°</b> | Rwy Ldg<br>TDZE <b>516</b><br>Apt Elev <b>516</b> |
|----------------------------------------|------------------------|---------------------------------------------------|

RNAV (GPS) RWY 32

WACO RGNL (ACT)

⚠

ASR

DME/DME RNP-0.3 NA. When local altimeter setting not received use Mc Gregor Exec altimeter setting and increase all DA 31 feet and all MDA 40 feet; increase LPV and LNAV/VNAV all Cats and LNAV Cats C/D visibility ⅓ mile and Circling Cat D visibility ¼ mile. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -13°C (9°F) or above 54°C (130°F). Baro-VNAV NA when using Mc Gregor Exec altimeter setting. VDP NA with Mc Gregor Exec altimeter setting.

MISSED APPROACH: Climb to 4000 direct EVVIS and hold, continue climb-in-hold to 4000.

|                       |                                         |                                          |                         |                         |
|-----------------------|-----------------------------------------|------------------------------------------|-------------------------|-------------------------|
| ATIS<br><b>123.85</b> | WACO APP CON ★<br><b>127.65 227.125</b> | WACO TOWER ★<br><b>119.3(CTAF) 257.8</b> | GND CON<br><b>121.9</b> | UNICOM<br><b>122.95</b> |
|-----------------------|-----------------------------------------|------------------------------------------|-------------------------|-------------------------|

