

WAAS CH 90299 W20A	APP CRS 202°	Rwy Ldg 6527 TDZE 1194 Apt Elev 1194
--	------------------------	---

RNAV (GPS) RWY 20
WALLA WALLA RGNL (ALW)

RNP APCH - GPS.




For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C or above 54°C. For inop ALS, increase LNAV/VNAV visibility to 1½ SM.
*RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR



MISSED APPROACH:
Climb to 4000 direct
CILON and hold.

ASOS 135.875	SPOKANE APP CON★ 133.15 379.15	WALLA WALLA TOWER★ 118.5 (CTAF) 289.4	GND CON 121.6 289.4	UNICOM 122.95
-----------------	-----------------------------------	--	------------------------	------------------



CILON

4000 ↑

5 NM Holding Pattern

022° → 10000
← 202° 4600

WACKE 3.7 NM to RW20

COSUV 3200

KIMIW


RW20 2.9 NM to RW20

2420 3200

GP 3.00°
TCH 50

2.9 NM 0.9 NM 2.4 NM 5.9 NM

CATEGORY		A	B	C	D
LPV	DA*	1394/24 200 (200-½)			
RNAV/ VNAV	DA	1773-1¼ 579 (600-1¼)			
RNAV MDA		2160/40 966 (1000-¾)	2160/55 966 (1000-1)	2160-2½	966 (1000-2½)
CIRCLING		2160-1¼ 966 (1000-1¼)	2160-1½ 966 (1000-1½)	2160-3 966 (1000-3)	2300-3 1106 (1200-3)

WALLA WALLA RGWL (ALW)
RNAV (GPS) RWY 20