

VORTAC DQO	APP CRS	Rwy Ldg	7000
114.0	261°	TDZE	72
Chan 87		Apt Elev	80

VOR RWY 27


NEW CASTLE (ILG)

⚠


Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Philadelphia Intl altimeter setting and increase all MDAs 60 feet; increase S-27 Cat B and Circling Cat C/D visibility ¼ SM and S-27 Cat C/D visibility ½ SM; WIROL fix minimums S-27 increase Cat C/D and Circling Cat D visibility ¼ SM.

MISSED APPROACH: Climb to 2000 on DQO VORTAC R-274 to GLEEM INT/DQO 5.1 DME and hold.

ATIS 123.95	PHILADELPHIA APP CON 118.35 323.1	WILMINGTON TOWER * 126.0 (CTAF) 352.05	GND CON 121.7 275.8	UNICOM 122.95
----------------	--------------------------------------	---	------------------------	------------------



ELEV 80	D	TDZE 72
---------	---	---------



REIL Rwys 9, 19 and 27 
HIRL Rwys 1-19 and 9-27 
MIRL Rwy 14-32 

FAF to MAP 5.9 NM					
Knots	60	90	120	150	180
Min:Sec	5:54	3:56	2:57	2:22	1:58

2000 ↑ DQO R-274		GLEEM INT		LEIDR INT DQO 5.9		One Minute Holding Pattern			
DQO VORTAC		WIROL DQO 2.9		1800		081° → 2100 ← 261°			
0.6		2.3		3 NM		* 860 when using Philadelphia Infl altimeter setting.			
CATEGORY		A		B		C		D	
S-27		800-1		728 (800-1)		800-2		728 (800-2)	
CIRCLING		800-1		720 (800-1)		800-2 720 (800-2)		800-2 ¼ 720 (800-2 ¼)	
WIROL FIX MINIMUMS (DME REQUIRED)									
S-27		560-1		488 (500-1)		560-1 ⅜		488 (500-1 ⅝)	
CIRCLING		560-1		480 (500-1)		600-1 ½ 520 (600-1 ½)		800-2 ¼ 720 (800-2 ¼)	