

WAAS CH 58006 W12A	APP CRS 121°	Rwy Ldg TDZE Apt Elev	7704 401 410
--	------------------------	-----------------------------	---

RNAV (GPS) Y RWY 12



TRI-CITIES (PSC)

RNP APCH - GPS.

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -14°C or above 54°C. Rwy 12 helicopter visibility reduction below ¾ SM NA. Baro-VNAV and VDP NA when using HRI altimeter setting. When local altimeter setting not received, use HRI altimeter setting: increase LPV DA to 696 feet and all visibilities ¼ SM, and increase LNAV/VNAV DA to 935 feet and all visibilities ¼ SM. Increase all MDAs 100 feet and LNAV and Circling Cats C and D visibility ¼ SM.

MISSED APPROACH: Climb to 900 then climbing left turn to 3200 direct CITYS and hold.

ATIS 125.65	SPOKANE APP CON ★ 128.75 377.2	TRI-CITIES TOWER ★ 135.3 (CTAF) 0 285.55	GND CON 121.8	UNICOM 122.95
-----------------------	--	--	-------------------------	-------------------------



Procedure NA for arrival on PSC VOR/DME airway radials 234 CW 020.				
HILOB 4 NM Holding Pattern 10000 3300 GP 3.00° TCH 53				
FAXAX 2200 ZAPOV 2.1 NM to RW12 1.2 NM to RW12 1100				
7 NM 3.5 NM 0.8 NM 1.2 NM				
CATEGORY	A	B	C	D
LPV DA	601-¾ 200 (200-¾)			
LNAV/VNAV DA	840-1¼ 439 (500-1¼)			
LNAV MDA	840-1	439 (500-1)	840-1¼	439 (500-1¼)
CIRCLING	900-1 490 (500-1)	940-1 530 (600-1)	1040-1¾ 630 (700-1¾)	1100-2¼ 690 (700-2¼)

NW-1, 27 NOV 2025 to 25 DEC 2025

NW-1, 27 NOV 2025 to 25 DEC 2025