

ILS or LOC RWY 31

LOC I-BNN 108.3	APCH CRS 308°	Rwy Idg 8194 TDZE 4270 Arprt Elev 4295	[USAF]	CANNON AFB (KCVS)
---------------------------	-------------------------	---	--------	-------------------

ATC RADAR or DME required. Missed approach requires use of RNAV or ATC RADAR monitoring.

*** When ALS inop, increase vis to ¾ mile.**

ATIS 119.1 269.9	CANNON APP CON 118.425 352.1	CANNON TOWER 120.4 270.25	GND CON 121.9 275.8	CLNC DEL 120.2 293.225
----------------------------	--	-------------------------------------	-------------------------------	----------------------------------

**** When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1 ½ miles.**

EMERG SAFE ALT 100 NM 9000

6000 ↑	LERAY CVS 5.5	7000 ↶	VGSI TCH (41') and the procedure TCH (51') is greater than 3'.	
-----------	----------------------------	-----------	--	--

CATEGORY	A	B	C	D	E
S-ILS 31*	4470-½				
S-LOC 31**	4660-½	390 (400-½)	4660-⅝	390 (400-⅝)	
CIRCLING	4840-1				
	545 (600-1)	4860-1½	5000-2¼	5020-2½	

Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:30